



Air Tools — Grinders

1/4" Angle Die Grinder, 90°

- Lightweight and durable
- Ergonomic composite housing with a soft comfortable grip
- Lower noise than aluminum tools while in operation
- Right angle provides easy access
- For sanding, polishing, deburring, and porting



Specifications:

Part No.	/EAG5202EC
Collet Size	1/4"
RPM — Approx.	20,000
Throttle Type	Lever
Exhaust	Rear
Weight	1.1 lb. / 0.55 kg
Length	6.25 in. / 15.9 cm
Approx. Power	0.60 hp
Air Usage	12 cfm
Air Inlet	1/4"

1/4" Angle Die Grinder

- Compact lightweight design
- Ball bearing construction
- For sanding, deburring, polishing
- Right angle provides easy access



Specifications:

Part No.	/EAG5003C
Collet Size	1/4"
RPM — Approx.	20,000
Throttle Type	Safety Lever
Exhaust	Rear
Weight	1.0 lb. / 0.5 kg
Length	6.3 in. / 15.9 cm
Approx. Power	0.33 hp
Air Usage	14 cfm
Air Inlet	1/4"

4.5" Angle Grinder

- Swivel guard adjustable in 9 steps
- Accepts 0.8mm - 6mm wheel
- Vibration reduction handle (optional)
- Composite body
- Spindle lock
- Quiet operation

- Rear exhaust
- Side handle



Specifications:

Part No.	/EAG5195EC
Spindle	5/8" - 11
RPM — Approx.	10,800
Throttle Type	Lever
Exhaust	Rear
Weight	3.8 lbs. / 1.72 kg
Length	9.6 in. / 24.4 cm
Approx. Power	1.30 hp
Air Usage	11 cfm
Air Inlet	1/4"

5" Angle Grinder

- Uses type 27 wheels, abrasive discs
- Rugged lightweight aluminum alloy housing
- Spiral bevel gearing for extended life, low vibration
- Removable dead handle
- For weld prep, smoothing, rust removal, deburring
- 5/8"-11 adapter included



Specifications:

Part No.	/EAG5007
Wheel Capacity	5"
Spindle Type	3/8" -24
RPM — Approx.	11,000
Throttle Type	Safety Lever
Exhaust	Front Right
Weight	4.0 lb. / 1.8 kg
Length	9.5 in. / 24.1 cm
Approx. Power	0.6 hp
Air Usage	18 cfm
Air Inlet	1/4"

Air Tools — Sanders

3" - 5" High Speed Sander

- Built-in regulator to control speed
- Lightweight, compact design
- Includes 3" and 5" backing pad
- For paint removal, shaping filler patches, weld smoothing, rust removal



Specifications:

Part No.	/EAG6113
Pad Size	3" and 5"
RPM — Approx.	18,000
Spindle	3/8"
Weight	2.4 lb. / 1.1 kg
Length	4.6 in. / 11.7 cm
Air Usage	19 cfm
Air Inlet	1/4"

Air Tools — Impact Wrenches

3/8" Impact Wrench

- Composite housing
- Twin hammer design
- Swivel air inlet fitting
- Large easy-to-use forward-reverse switch
- Bottom grease fitting
- Same as /2258EC with 3/8" square drive
- **Approx. Working Torque — 189 ft.-lb.**



Specifications:

Part No.	/EAG2163EC
Drive Size	3/8"
RPM — Approx.	10,400
Torque Range — Approx.	131-189 ft.-lb. / 178-256 Nm
Max Torque	220 ft.-lb. / 298 Nm
Weight	2.7 lb. / 1.2 kg
Length	6.5 in. / 16.5 cm
Air Usage	15 cfm
Air Inlet	1/4"



Air Tools — Impact Wrenches

(Cont.)

1/2" Impact Wrench

- Composite housing
- Twin hammer design
- Large easy-to-use forward-reverse switch
- Bottom grease fitting
- Swivel air inlet fitting
- **Approx. Working Torque — 295 ft.-lb.**



Specifications:

Part No.	/EAG2263EC
Drive Size	1/2"
RPM — Approx.	7,800
Torque Range — Approx.	210-295 ft.-lb. / 284-400 Nm
Max Torque	333 ft.-lb. / 452 Nm
Weight	4.5 lb. / 2.0 kg
Length	8.2 in. / 20.8 cm
Air Usage	19 cfm
Air Inlet	1/4"

3/4" Impact Wrench

- Composite housing
- Twin hammer design
- Large easy-to-use forward-reverse switch
- Bottom grease fitting
- Swivel air inlet fitting
- **Approx. Working Torque — 850 ft.-lb.**



Specifications:

Part No.	/EAG2375EC
Drive Size	3/4"
RPM — Approx.	5,500
Torque Range — Approx.	500-885 ft.-lb. / 368-1,200 Nm
Max Torque	1,125 ft.-lb. / 1,525 Nm
Weight	7.8 lb. / 3.5 kg
Length	9.4 in. / 24 cm
Air Usage	27 cfm
Air Inlet	3/8"

Air Tools — Drills

3/8" And 1/2" Drill — Non-Reversible

- Positive action trigger controls speed
- For drilling, counter sinking, and wire brushing



Specifications:

Part No.	/EAG7107	/EAG7105
Chuck Capacity	3/8"	1/2"
RPM — Approx.	2,600	500
Weight	4.0 lb. / 1.8 kg	4.0 lb. / 1.8 kg
Length	7.0 in. / 17.8 cm	7.0 in. / 17.8 cm
Air Usage	20 cfm	20 cfm
Air Inlet	1/4"	1/4"

Air Tools — Hammers

Air Hammer

- Economical air hammer for fast cutting action
- For muffler and pipe removal, body shop work, shock work, scraping rust, light front-end work
- For exhaust system, panel cutting, general repair work
- Includes 6" chisel with 1-3/8" angled blade



Specifications:

Part No.	/EAG4001
For Use With	Chisel
Chisel Diameter	0.401 in.
Bore	0.75 in.
Stroke	2.625 in.
BPM — Approx.	3,500
Weight	3.8 lb. / 1.7 kg
Length	6.8 in. / 17.1 cm
Air Usage	15 cfm
Air Inlet	1/4"

Air Tools — Ratchet Wrenches

1/2" And 3/8" Ratchet Wrenches

- Excellent for extended uages
- Improved gear head extends life
- Power for tough jobs
- **Approx. Working Torque — 55 ft.-lbs.**



Specifications:

Part No.	/EAG3105	/EAG3100
CDrive Size	1/2"	3/8"
RPM — Approx.	150	160
Torque — Approx.	55 ft.-lb. / 74 Nm	25 ft.-lb. / 33 Nm
Weight	3.1 lb. / 1.4 kg	2.6 lb. / 1.2 kg
Length	14.5 in. / 36.8 cm	10.5 in. / 26.7 cm
Air Usage	21 cfm	16 cfm
Air Inlet	1/4"	1/4"

“In times like these, it helps to recall that there have always been times like these.”
 —Paul Harvey

“The right to do something does not mean that doing it is right.”
 —William Safire